

Safety Data Sheet

Methanol 70%, (v/v)

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Methanol 70%, (v/v)

Synonyms/Generic Names: Methyl Alcohol

Product Number: 9011

Product Use: Industrial, Manufacturing or Laboratory use

Manufacturer: Columbus Chemical Industries, Inc.

N4335 Temkin Rd. Columbus, WI. 53925

For More Information: 920-623-2140 (Monday-Friday 8:00-4:30)

www.columbuschemical.com

In Case of Emergency Call: CHEMTREC - 800-424-9300 or 703-527-3887 (24 Hours/Day, 7 Days/Week)

2. HAZARDS IDENTIFICATION

Hazard Not Otherwise Classified (HNOC): None

Target Organs: Respiratory system, Central nervous system

Signal Words: Danger

Pictograms:







GHS Classification:

Flammable liquids	Category 2
Skin irritation	Category 2
Eye irritation	Category 2A
Specific target organ toxicity – single exposure	Category 2

GHS Label Elements, including precautionary statements:

Hazard Statements:

•	uzura Otalomonio.		
	H225	Highly flammable liquid and vapor.	
H315+H320 Causes skin and eye irritation.		Causes skin and eye irritation.	
H370 Causes damage to organs.		Causes damage to organs.	

Precautionary Statements:

P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.	

Revised on 04/18/2022 Page 1 of 7

P233	Keep container tightly closed.	
P240	Ground/Bond container and receiving equipment.	
P241	Use explosion-proof electrical/ventilating/lighting/equipment.	
P242	Use only non-sparking tools.	
P243	Take precautionary measures against static discharge.	
P260	Do not breathe dust/fume/gas/mist/vapors/spray.	
P264	Wash hands thoroughly after handling.	
P270	Do not eat, drink or smoke when using this product.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse	
	skin with water/shower.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove	
	contact lenses, if present and easy to do. Continue rinsing.	
P332+P313	If skin irritation occurs: Get medical advice/attention.	
P337+P313	If eye irritation persists: Get medical advice/attention.	
P362+P364	Take off contaminated clothing and wash it before reuse.	
P370+P378	In case of fire: Use appropriate media to extinguish.	
P403+P235	Store in a well-ventilated place. Keep cool.	
P405	Store locked up.	
P501	Dispose of contents/container in accordance with local regulations.	

Potential Health Effects

Eyes	Causes irritation.	
Inhalation	n May be harmful if inhaled. Causes respiratory tract irritation	
Skin	Toxic if absorbed through skin. Causes skin irritation.	
Ingestion	Toxic if swallowed.	

NFPA Ratings

Health	1
Flammability	3
Reactivity	0
Specific hazard	Not Available

HMIS Ratings

Health	2
Fire	3
Reactivity	0

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight %	CAS#	EINECS# / ELINCS#	Formula	Molecular Weight
Methyl Alcohol	70-75	67-56-1	200-659-6	CH₃OH	32.04 g/mol
Water	25-30	7732-18-5	231-791-2	H ₂ O	18.00 g/mol

4. FIRST-AID MEASURES

Eyes	Rinse with plenty of water for at least 15 minutes and seek medical attention.		
Inhalation	Move casualty to fresh air and keep at rest. If breathing is difficult, give oxygen. If not		
	breathing, give artificial respiration. Get medical attention.		
Skin	Flush with plenty of water for at least 15 minutes while removing contaminated clothing and		
	wash using soap. Get medical attention.		
Ingestion	Do Not Induce Vomiting! Never give anything by mouth to an unconscious person. If		
	conscious, wash out mouth with water. Get medical attention.		

Revised on 04/18/2022 Page 2 of 7

5. FIREFIGHTING MEASURES

Suitable (and unsuitable) extinguishing media	Product is flammable. Use carbon dioxide, alcohol-type foam or dry chemical. Cool containers with water.	
Special protective equipment and precautions for firefighters	Wear self-contained, approved breathing apparatus and full protective clothing, including eye protection and boots.	
Specific hazards arising from the chemical	Emits toxic fumes (carbon oxides) under fire conditions. Sealed containers may explode if exposed to high heat or fire. See also Stability and Reactivity section.	

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	See section 8 for recommendations on the use of personal protective equipment.
Environmental precautions	Prevent spillage from entering drains. Any release to the environment may be subject to a federal/national or local reporting requirements.
Methods and materials for containment and cleaning up	Absorb spill with noncombustible absorbent material, then place in a suitable container for disposal. Clean surfaces thoroughly with water to remove residual contamination. Dispose of all waste and cleanup materials in accordance with regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. Keep away from sources of ignition- No Smoking. Take measure to prevent the buildup of electrostatic charge. See section 8 for recommendations on the use of personal protective equipment. Use with adequate ventilation. Wash thoroughly after using. Keep container closed when not in use.

Conditions for safe storage, including any incompatibilities

Store in cool, dry well ventilated area in tightly-closed, plainly-labeled containers. Store between 55-100°F for product stability. Do not store with strong oxidizing agents, strong acids, peroxides, aldehydes, halogens, ammonia, acid anhydrides or alkali metals. Keep away from incompatible materials (see section 10 for incompatibilities).

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational exposure controls: Ventilation and appropriate grounding of container.

Component	Exposure Limits	Basis	Entity
Methyl Alcohol	200 ppm 262 mg/m ³	TLV	ACGIH
	250 ppm 328 mg/m ³	STEL	ACGIH
	200 ppm 260 mg/m ³	PEL	OSHA
	200 ppm 260 mg/m ³	REL	NIOSH
	250 ppm	STEL	NIOSH

Revised on 04/18/2022 Page 3 of 7

325 mg/m ³	

TWA: Time Weighted Average over 8 hours of work. TLV: Threshold Limit Value over 8 hours of work.

REL: Recommended Exposure Limit PEL: Permissible Exposure Limit

STEL: Short Term Exposure Limit during x minutes. IDLH: Immediately Dangerous to Life or Health WEEL: Workplace Environmental Exposure Levels

CEIL: Ceiling

Personal Protection

Eyes	Wear chemical safety glasses with face shield.
Inhalation	Provide local exhaust, preferably mechanical. If exposure levels are excessive, use an
	approved respirator.
Skin	Wear nitrile or rubber gloves, apron or lab coat.
Other	Not Available

Other Recommendations

Provide eyewash stations, quick-drench showers and washing facilities accessible to areas of use and handling. Have supplies and equipment for neutralization and running water available.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.)	Clear, colorless liquid
Odor	Mild alcohol
Odor threshold	Not Available
pH	6.7
Melting point/freezing point	Not Available
Initial boiling point and boiling range	74°C (165°F)
Flash point	16°C (60°F) closed cup
Evaporation rate	Not Available
Flammability (solid, gas)	Flammable
Upper/lower flammability or explosive limit	LFL: 6.0% UFL: 36.0% (methanol >99%)
Vapor pressure	Not Available
Vapor density	1.11 (air=1)
Specific gravity	0.8769
Solubility (ies)	Completely soluble in water
Partition coefficient: n-octanol/water	Not Available
Auto-ignition temperature	Not Available
Decomposition temperature	Not Available

10. STABILITY AND REACTIVITY

Chemical Stability	Stable
Possibility of Hazardous Reactions	Will not occur.
Conditions to Avoid	Temperatures below 32°F or above 90°F
Incompatible Materials	Strong oxidizing agents, strong acids, peroxides, aldehydes,
	halogens, ammonia, acid anhydrides or alkali metals
Hazardous Decomposition Products	Carbon oxides.

Revised on 04/18/2022 Page 4 of 7

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Methanol

Skin	LD50 Dermal- rabbit- 15,800 mg/kg
Eyes	Eyes- rabbit- Eye irritation- 24 hour
Respiratory	LC ₅₀ rat- 85 mg/L, 4 hours
	LC ₅₀ rat- 64000 ppm, 4 hours
Ingestion	LD ₅₀ rat- 5,628 mg/kg

Carcinogenicity

IARC	No components of this product present at levels greater than or equal to 0.1% is
	identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	No components of this product present at levels greater than or equal to 0.1% is
	identified as a carcinogen or potential carcinogen by ACGIH.
NTP	No components of this product present at levels greater than or equal to 0.1% is
	identified as a known or anticipated carcinogen by NTP.
OSHA	No components of this product present at levels greater than or equal to 0.1% is
	identified as a carcinogen or potential carcinogen by OSHA.

Signs & Symptoms of Exposure

Skin	Burning, itching, redness may be harmful if absorbed through skin.
Eyes	Causes irritation. Redness, excessive blinking and watering eyes.
Respiratory	Coughing, wheezing, headache, disorientation, blurred vision, dizziness, fatigue or
	nausea.
Ingestion	Nausea, vomiting, may cause blindness and central nervous system depression.

Chronic Toxicity	Ingestion may cause blindness
Teratogenicity	Not Available
Mutagenicity	Not Available
Embryotoxicity	Pre-and Post- implant mortality
Target Organ(s)	Respiratory system, Central nervous system
Reproductive Toxicity	Not Available
Respiratory/Skin Sensitization	Not Available

12. ECOLOGICAL INFORMATION

Ecotoxicity

Methanol

IVICTIATION		
Aquatic Vertebrate	Do not release directly into surface water	
	LC ₅₀ = 15,400 mg/L, 96 hours (Lepomis Macrochirus)	
	LC50- Oncorhynchus mykiss (rainbow trout)- 19,000 mg/l- 96 h	
	LC50- Cyprinus carpio (Carp)- 36,000.00 mg/l- 48 h	
Aquatic	EC50- Daphnia magna (Water flea)- 24,500.00 mg/l- 48 h	
Invertebrate	EC100- Daphnia magna (Water flea)- 10,000.00 mg/l- 24 h	
Terrestrial	Not Available	

Persistence and Degradability	Not Available
Bioaccumulative Potential	BCF of 1
Mobility in Soil	Not Available
PBT and vPvB Assessment	Not Available
Other Adverse Effects	Not Available

Revised on 04/18/2022 Page 5 of 7

13. DISPOSAL CONSIDERATIONS

Waste Product or	Users should review their operations in terms of the applicable federal/national or
Residues	local regulations and consult with appropriate regulatory agencies if necessary
	before disposing of waste product or residue.
Product	Users should review their operations in terms of the applicable federal/national or
Containers	local regulations and consult with appropriate regulatory agencies if necessary
	before disposing of waste product container.

The information offered in section 13 is for the product as shipped. Use and/or alterations to the product may significantly change the characteristics of the material and alter the waste classification and proper disposal methods.

14. TRANSPORTATION INFORMATION

US DOT	UN1230, Methanol solution, 3, pg II
TDG	UN1230, METHANOL SOLUTION, 3, PG II
IMDG	UN1230, METHANOL SOLUTION, 3, pg II
Marine Pollutant	No
IATA/ICAO	UN1230, Methanol solution, 3 pg II

15. REGULATORY INFORMATION

TSCA Inventory Status	All ingredients are listed on the TSCA Active
	inventory.
DSL / NDSL	All ingredients are listed on the DSL inventory.
California Proposition 65	Listed: Methyl Alcohol
Rhode Island: Hazardous Substance List	Listed: Methyl Alcohol
Massachusetts: Toxic or Hazardous Substance List,	Listed: Methyl Alcohol
Right to Know	
Pennsylvania: Hazardous Substance List	Listed: Methyl Alcohol
New Jersey: Right to Know Hazardous Substance	Listed: Methyl Alcohol
List	
SARA 302	Not Listed
SARA 304	Not Listed
SARA 311	Fire Hazard, Acute Health Hazard, Chronic Health
	Hazard.
SARA 312	Fire Hazard, Acute Health Hazard, Chronic Health
	Hazard.
SARA 313	Listed: Methyl Alcohol
WHMIS Canada	Class B2: Flammable and combustible material –
	Flammable liquid.
	Class D1B: Poisonous and infectious material –
	Immediate and serious effects – Toxic.
	Class D2A: Poisonous and infectious material –
	Other effects – Very toxic.
	Class D2B: Poisonous and infectious material –
	Other effects – Toxic.

Revised on 04/18/2022 Page 6 of 7

16. OTHER INFORMATION

Revision	Date
Original	07/08/2011
Revision 1	10/29/2013
Revision 2	02/25/2015
Revision 3	09/26/2018
Revision 4	04/18/2022

Disclaimer: The information provided in this Safety Data Sheet ("SDS") is correct to the best of our knowledge, information, and belief at the date of publication. The information in this SDS relates only to the specific Product identified under Section 1, and does not relate to its use in combination with other materials or products, or its use as to any particular process. Those handling, storing, or using the Product should satisfy themselves that they have current information regarding the particular way the Product is handled, stored or used and that the same is done in accordance with federal, state and local law. WE DO NOT MAKE ANY WARRANTY, EXPRESS OR IMPLIED, INCLUDING (WITHOUT LIMITATION) WARRANTIES WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN OR WITH RESPECT TO FITNESS FOR ANY PARTICULAR USE. WE DO NOT ASSUME RESPOSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, INJURY, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THIS PRODUCT.

Revised on 04/18/2022 Page 7 of 7